

**DATA SHEET**
**EARTH LEAKAGE DETECTOR**

<b>TYPE:</b>	<b>TST2706B</b>
--------------	-----------------

**ELECTRICAL CHARACTERISTICS:**

INPUT VOLTAGE	NOMINAL:	230 VAC
	MIN - MAX	180 – 260 VAC

**MECHANICAL CHARACTERISTICS:**

MATERIAL OF THE PC-BOARD:	FR-4
MATERIAL OF THE CASING:	ALUMINIUM
CONNECTORS:	SCREW CONNECTOR 2,5mm2

**ENVIRONMENTAL CONDITIONS:**

AMBIENT TEMPERATURE RANGE:	CONTINUOUS OPERATION:	+10°C ... +50°C
	STORAGE:	-40°C ... +70°C

**SPECIAL FEATURES:**

Detects earth leakage (alarm triggers if leakage current is over 30 mA), alarm output to central module.
--

WRITTEN BY:	05.02.2009 / MK	UPDATED BY:	
CHECKED BY:		CHECKED BY:	
APPROVED BY:		APPROVED BY:	

We reserve the right to make modifications without prior notice

Teknoware Oy, Ilmarisentie 8, FI-15200 LAHTI, FINLAND  
Tel. +358 3 883 020, www.teknoware.fi

Vehicle lighting: fax +358 3 8830 240, e-mail sales@teknoware.fi  
Emergency lighting: fax +358 3 8830 260, e-mail emexit@teknoware.fi